SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SDI NEW Product code : 504.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Degreasing solvent

Professional use

1.3. Details of the supplier of the safety data sheet

Registered company name : ORAPI.

Address : PARC INDUSTRIEL DE LA PLAINE DE L'AIN - 225 ALLEE DES CEDRES.01150.SAINT-VULBAS.FRANCE. Telephone : 33-(0)4-74-40-20-20. Fax : 33-(0)4-74-40-20-21.

fds@orapi.com

1.4. Emergency telephone number : 33-(0)1-45-42-59-59.

Association/Organisation : INRS .

Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Carcinogenicity, Category 2 (Carc. 2, H351).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



CUSO7



CHEUS

GHS07	GHS08	
Signal Word :		
WARNING		
Product identifiers	8:	
EC 200-838-9	DICHLOROM	1ETHANE
EC 232-433-8	ORANGE, SW	VEET, EXT.
Hazard statements	:	
H315		Causes skin irritation.
H317		May cause an allergic skin reaction.
H319		Causes serious eye irritation.
H336		May cause drowsiness or dizziness.
H351		Suspected of causing cancer .
H412		Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :					
P201	Obtain special instructions before use.				
P260	Do not breathe mist, vapours.				
P273	Avoid release to the environment.				
P280	Wear protective gloves/protective clothing/eye protection/face protection.				
Precautionary statements - Response :					
P308 + P313	IF exposed or concerned: Get medical advice/attention.				
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.				
Other information :					

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Composition .			
Identification	(EC) 1272/2008	Note	%
INDEX: 1254	GHS07, GHS08	[1]	50 <= x % < 100
CAS: 75-09-2	Wng	[2]	
EC: 200-838-9	Skin Irrit. 2, H315		
REACH: 01-2119480404-41	Eye Irrit. 2, H319		
	STOT SE 3, H336		
DICHLOROMETHANE	Carc. 2, H351		
INDEX: 0030	GHS07, GHS09, GHS08, GHS02		0 <= x % < 2.5
CAS: 8028-48-6	Dgr		
EC: 232-433-8	Flam. Liq. 3, H226		
	Asp. Tox. 1, H304		
ORANGE, SWEET, EXT.	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Aquatic Acute 1, H400		
	M Acute $= 1$		
	Aquatic Chronic 1, H410		
	M Chronic $= 1$		

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Consult a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

Consult a doctor.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital. Consult a doctor in the event of irritation.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

- In the event of a fire, do not use :
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- phosgene (CCl2O)
- hydrogen chloride (HCl)
- chlorine (Cl2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothings.

Do not breathe vapours, fumes and mist.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Keep the container away from heat, bad weather, dampness and freezing.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2017/164/UE, 2009/161/UE, 2006/15/CE, 2000/39/CE, 98/24/CE)							
CAS	VME-mg/m3:	VME-ppm :	VLE-mg/m3:	VLE-ppm :	Notes :]	
75-09-2	353	100	706	200	Skin		
- ACGIH TLV (Ame	erican Conferen	ce of Governme	ental Industrial l	Hygienists, Thre	eshold Limit Va	lues, 2010) :	
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :]	
75-09-2	50 ppm			A3; BEI			
- Germany - AGW (BAuA - TRGS	900, 21/06/2010)):				
CAS	VME :	VME :	Excess	Notes			
75-09-2		50 ppm		2 (II)			
		180 mg/m3					
- France (INRS - ED984 :2012) :							
CAS	VME-ppm :	VME-mg/m3:	VLE-ppm :	VLE-mg/m3:	Notes :	TMP No :	
75-09-2	50	178	100	356	C2,*	12	

	WEL (Work		limits, EH40/20					
CAS		TWA :	STEL :	Ceiling :	Definition :	Criteria :		
75-09-	-2	100 ppm 350 mg/m3	300 ppm 1060 mg/m3		Bmgv Sk			
Derived	no effect lev		lerived minimu	ım effect level	(DMEL):			
DIO	CHLOROME	ETHANE (CAS	: 75-09-2)					
	nal use:			Work				
	Exposure met			Dermal c				
	Potential heal	th effects:			m systemic effec			
I	ONEL :			4750 mg	/kg body weight	/day		
	Exposure met			Inhalatio				
	Potential heal	th effects:			m systemic effec	ets.		
Ι	ONEL :			706 mg o	of substance/m3			
	Exposure met			Inhalatio				
	Potential heal	th effects:			m systemic effec	ts.		
I	ONEL :			353 mg (of substance/m3			
	nal use:				imers.			
	Exposure met			Dermal c				
	Potential heal	th effects:		Long term systemic effects.				
I	ONEL :			2395 mg/kg body weight/day				
	Exposure met			Inhalation.				
-	Potential heal	th effects:		Short term systemic effects.				
I	ONEL :			353 mg of substance/m3				
Predicte	d no effect c	oncentration (PNEC):					
DIC	CHLOROME	ETHANE (CAS	: 75-09-2)					
E	Environmenta	al compartment	:	Soil. 0.583 mg/kg				
F	PNEC :							
E	Environmenta	al compartment	:	Fresh water.				
F	PNEC :			0.54 mg/l				
E	Environmenta	al compartment	:	Sea water.				
F	PNEC :			0.194 mg/l				
E	Environmenta	al compartment	:	Intermittent waste water.				
F	PNEC :			0.27 mg/l				
F	Environmenta	al compartment	:	Fresh wa	ter sediment.			
	PNEC :	1		4.47 mg/kg				
F	Environmenta	al compartment	:	Marine s	ediment.			
	PNEC :	-		1.61 mg/kg				
E	Environmenta	al compartment	:	Waste wa	ater treatment pla	ant.		
	PNEC :	-		26 mg/l				
8 7 Frm	osure contro	Je						
о. <i>2</i> . ехр	osure contro	115						

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)
- Silver Shield ® (Polyethylene / Ethylene-Vinyl-Alcohol (PE / EVOH))
- Teflon® (Polytetrafluoroethylene (PTFE))
- Viton® (Hexafluoropropylene copolymer and vinylidene fluoride)
- Recommended properties :
- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- AX (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :			
Physical state :	Fluid liquid.		
Important health, safety and environmental information			
pH :	Not relevant.		
Boiling point/boiling range :	Not relevant.		
Flash point interval :	Not relevant.		
Vapour pressure (50°C) :	Not relevant.		
Density :	1.3		
Water solubility :	Insoluble.		
Melting point/melting range :	Not specified.		
Self-ignition temperature :	Not relevant.		
Decomposition point/decomposition range :	Not specified.		

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- heat
- flames and hot surfaces
- sources of ignition

10.5. Incompatible materials

- Keep away from :
- oxidising agents
- metals
- strong acids
- strong bases

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- phosgene (CCl2O)
- hydrogen chloride (HCl)
- chlorine (Cl2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance. May cause an allergic reaction by skin contact.

Suspected human carcinogen.

11.1.1. Substances

Acute toxicity :

DICHLOROMETHANE (CAS: 75-09-2) Oral route :

LD50 > 2000 mg/kg Species : Rat

Dermal route :	LD50 > 2000 mg/kg
	Species : Rat

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

DICHLOROMETHANE (CAS: 75-09-2) Fish toxicity :

LC50 = 193 mg/l Species : Pimephales promelas Duration of exposure : 96 h

NOEC = 83 mg/l Species : Pimephales promelas Duration of exposure : 28 days

Crustacean toxicity :

EC50 = 27 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ORANGE, SWEET, EXT. (CAS: 8028-48-6) Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

DICHLOROMETHANE (CAS: 75-09-2) Biodegradability :

Rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

2810

14.2. UN proper shipping name

UN2810=TOXIC LIQUID, ORGANIC, N.O.S. (dichloromethane, orange, sweet, ext.)

14.3. Transport hazard class(es)

- Classification :



6.1

14.4. Packing group

III

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	6.1	T1	III	6.1	60	5 L	274 614	E1	2	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	6.1	-	III	5 L	F-A,S-A	223 274	E1			

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	6.1	-	III	655	60 L	663	220 L	A3 A4	E1
								A137	
	6.1	-	III	Y642	2 L	-	-	A3 A4	E1
								A137	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG. For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : aliphatic hydrocarbons
- 30 % and more : halogenated hydrocarbons
- perfumes
- allergenic fragrances :
- (r)-p-mentha-1,8-diene

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.