#### **ORANET B10 - 5153**

Date: 19/07/2021 Page 1/11

Revision: N°1 (19/07/2021)

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name: ORANET B10

Product code: 5153.

UFI: WR02-D0CV-E007-Q658

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaner

Professional use

## 1.3. Details of the supplier of the safety data sheet

Registered company name: ORAPI.

Address: PARC INDUSTRIEL DE LA PLAINE DE L'AIN - 225 ALLEE DES CEDRES.01150.SAINT-VULBAS.FRANCE.

Telephone: 33-(0)4-74-40-20-20. Fax: 33-(0)4-74-40-20-21.

fds@orapi.com

## 1.4. Emergency telephone number: 33-(0)1-45-42-59-59.

Association/Organisation: INRS.

### Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).

Skin corrosion, Category 1 (Skin Corr. 1, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

Detergent mixture (see section 15).

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS05

Signal Word : DANGER

Product identifiers:

EC 215-181-3 POTASSIUM HYDROXIDE

 $Hazard\ statements:$ 

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements - Prevention :

P260 Do not breathe mist, vapours.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Precautionary statements - Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

#### **ORANET B10 - 5153**

Date: 19/07/2021 Page 2/11

Revision: N°1 (19/07/2021)

P310 Immediately call a POISON CENTER or doctor/physician.

P390 Absorb spillage to prevent material damage.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

**Composition:** 

Identification	(EC) 1272/2008	Note	%
CAS: 9005-65-6			2.5 <= x % < 10
EC: 500-019-9	Aquatic Chronic 3, H412		
SORBITAN MONOOLEATE,			
ETHOXYLATED			
INDEX: 011-005-00-2	GHS07		$2.5 \le x \% < 10$
CAS: 497-19-8	Wng		
EC: 207-838-8	Eye Irrit. 2, H319		
REACH: 01-2119485498-19			
SODIUM CARBONATE			
CAS: 1310-58-3	GHS07, GHS05	[1]	$2.5 \le x \% < 10$
EC: 215-181-3	Dgr		
REACH: 01-2119487136-33	Met. Corr. 1, H290		
	Acute Tox. 4, H302		
POTASSIUM HYDROXIDE	Skin Corr. 1A, H314		
CAS: 68515-73-1	GHS05		$2.5 \le x \% < 10$
EC: 500-220-1	Dgr		
REACH: 01-2119488530-36	Eye Dam. 1, H318		
D-GLUCOPYRANOSE, OLIGOMERIC,			
DECYL OCTYL GLYCOSIDES			
CAS: 68891-38-3	GHS05		$1 \le x \% < 2.5$
EC: 500-234-8	Dgr		
REACH: 01-2119488639-16	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
ALCOHOLS, C12-14, ETHOXYLATED,	Aquatic Chronic 3, H412		
SULFATES, SODIUM SALTS			
CAS: 34590-94-8		[1]	$1 \le x \% < 2.5$
EC: 252-104-2			
REACH: 01-2119450011-60			
(2 METHOVYMETHYLETHOVYORDORAN			
(2-METHOXYMETHYLETHOXY)PROPAN			
OL			

(Full text of H-phrases: see section 16)

# Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

## **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

# In the event of exposure by inhalation:

Move the person to fresh air.

Consult a doctor in case of disorder.

# In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

## **ORANET B10 - 5153**

Date: 19/07/2021 Page 3/11

Revision: N°1 (19/07/2021)

## In the event of splashes or contact with skin:

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Rinse immediately with plenty of water.

Consult a doctor if irritation occurs.

## In the event of swallowing:

Do not give the patient anything orally.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

#### 4.2. Most important symptoms and effects, both acute and delayed

See section 11.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxides (NOx)
- sulfur oxides

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

# For non first aid worker

Avoid any contact with the skin and eyes.

## For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

# 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Revision : N°1 (19/07/2021)

Date: 19/07/2021 Page 4/11

## 6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

**ORANET B10 - 5153** 

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

## **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Avoid contact with skin, eyes and clothings.

Do not breathe vapors, fumes, mists.

#### Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

## Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### **Packaging**

Always keep in packaging made of an identical material to the original.

## 7.3. Specific end use(s)

No data available.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

## Occupational exposure limits:

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
	:				
34590-94-8	308	50	-	1	Peau

- Belgium (Arrêté du 19/11/2020) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
1310-58-3		2 mg/m³		M	
34590-94-8	100 ppm	150 ppm		Skin	

- France (INRS - ED984 / 2020-1546):

CAS	VME-ppm:	VME-mg/m3	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
		:				
1310-58-3	-	-	-	2	-	-
34590-94-8	50	308	-	-	*	84

**ORANET B10 - 5153** 

Date: 19/07/2021 Page 5/11

Revision: N°1 (19/07/2021)

## - Switzerland (SUVAPRO 2019) :

CAS	VME	VLE	Valeur plafond	Notations
1310-58-3	2 ppm			
34590-94-8	100 ppm	150 ppm		Skin

## - UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
1310-58-3		2 mg/m³			
34590-94-8	50 ppm			Sk	
	308 mg/m <sup>3</sup>				

## Derived no effect level (DNEL) or derived minimum effect level (DMEL):

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 283 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 308 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 36 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 121 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects. DNEL: 37.2 mg of substance/m3

# POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Final use: Workers.
Exposure method: Inhalation.

Potential health effects: Long term local effects.

DNEL: 1 mg of substance/m3

Final use: Consumers. Exposure method: Inhalation.

Potential health effects: Long term local effects.

DNEL: 1 mg of substance/m3

SODIUM CARBONATE (CAS: 497-19-8)

Final use: Workers.

Exposure method: Inhalation.

Potential health effects: Long term local effects. DNEL: 10 mg of substance/m3

Final use: Consumers.
Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL: 10 mg of substance/m3

Version: N°1 (19/07/2021)

ORAPI

ORANET B10 - 5153

Date: 19/07/2021 Page 6/11

Revision: N°1 (19/07/2021)

## Predicted no effect concentration (PNEC):

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Environmental compartment: Soil. PNEC: 2.74 mg/kg

Environmental compartment: Fresh water. PNEC: 19 mg/l

Environmental compartment: Sea water. PNEC: 1.9 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 190 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 70.2 mg/kg

Environmental compartment: Marine sediment. PNEC: 7.02 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 4168 mg/l

## 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

# - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)

Recommended properties:

- Impervious gloves in accordance with standard EN ISO 374-2

# - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Version: N°1 (19/07/2021)

**ORAPI** 

#### **ORANET B10 - 5153**

Date: 19/07/2021 Page 7/11

Revision: N°1 (19/07/2021)

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## - Respiratory protection

In the event of insufficient ventilation, carry a respiratory apparatus of protection.

Respiratory protection in the presence of aerosol or of fog of product.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

#### **General information:**

Physical state: Fluid liquid.

## Important health, safety and environmental information

pH: Not stated.

Strongly basic.

Boiling point/boiling range:

Flash point interval:

Not relevant.

Vapour pressure (50°C):

Not relevant.

Vapour pressure (30 C):

Density:

1.1

Water solubility:

Melting point/melting range:

Not specified.

Self-ignition temperature:

Not specified.

Decomposition point/decomposition range:

Not specified.

## 9.2. Other information

No data available.

# **SECTION 10: STABILITY AND REACTIVITY**

## 10.1. Reactivity

Mixture which by chemical action can corrode and even destroy metals.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

## 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Avoid:

- frost

# 10.5. Incompatible materials

Keep away from:

- acids
- oxidising agents
- metals

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxides (NOx)
- sulfur oxides

## **ORANET B10 - 5153**

Date: 19/07/2021 Page 8/11

Revision: N°1 (19/07/2021)

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Ingestion can cause severe burns to the mouth, throat, disgesive system, as well as a danger of perforation of the esophagus and stomach.

## 11.1.1. Substances

## Acute toxicity:

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Oral route: LD50 = 8740 mg/kg

Species: Rat

Dermal route : LD50 = 9510 mg/kg

Species: Rabbit

Inhalation route (Vapours): LC50 = 3404.47 mg/l

Species: Rat

Duration of exposure: 4 h

#### 11.1.2. Mixture

## Skin corrosion/skin irritation:

Corrosive classification is based on an extreme pH value.

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

## 12.1.1. Substances

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Algae toxicity: NOEC = 0.95 mg/l

Duration of exposure: 72 h

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Fish toxicity: LC50 > 1000 mg/l

Species: Poecilia reticulata Duration of exposure: 96 h

Crustacean toxicity: EC50 = 1919 mg/l

Species : Daphnia magna Duration of exposure : 48 h

NOEC = 0.5 mg/l Species : Daphnia magna Duration of exposure : 21 days

Algae toxicity: ECr50 > 969 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

## **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

#### **ORANET B10 - 5153**

Date: 19/07/2021 Page 9/11

Revision: N°1 (19/07/2021)

## 12.2. Persistence and degradability

#### 12.2.1. Substances

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8) Biodegradability: Rapidly degradable.

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Biodegradability: Rapidly degradable.

#### 12.3. Bioaccumulative potential

## 12.3.1. Substances

(2-METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8) Octanol/water partition coefficient : log Koe = 1.01

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

No data available.

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

## 14.1. UN number

3267

# 14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(potassium hydroxide, d-glucopyranose, oligomeric, decyl octyl glycosides)

# 14.3. Transport hazard class(es)

- Classification:



8

# 14.4. Packing group

Π

## 14.5. Environmental hazards

\_

Version: N°1 (19/07/2021)

**ORAPI** 

Revision : N°1 (19/07/2021)

Date: 19/07/2021 Page 10/11

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	II	8	80	1 L	274	E2	2	Е

**ORANET B10 - 5153** 

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	8	-	П	1 L	F-A, S-B	274	E2	Category B SW2	SGG18 SG35

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)

#### - Container information:

No data available.

#### - Particular provisions:

No data available.

## - Labelling for detergents (EC Regulation No. 648/2004,907/2006):

- 5 % or over but less than 15 % : nonionic surfactants

## 15.2. Chemical safety assessment

No data available.

#### **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

## Wording of the phrases mentioned in section 3:

H290 May be corrosive to metals. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

#### Abbreviations :

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

UFI: Unique Formula Identifier
STEL: Short-term exposure limit
TWA: Time Weighted Averages
TMP: French Occupational Illness table
TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

Version: N°1 (19/07/2021)

**ORAPI** 

**ORANET B10 - 5153** 

Date: 19/07/2021 Page 11/11 Revision: N°1 (19/07/2021)

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

GHS05: Corrosion

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.