

TECHNICAL DATA SHEET

TDS 535 / Index 01 - 15/09/2014

535



ORARENOV

STAINLESS STEEL - ALUMINIUM STRIPPER / BRIGHTENER

MULTI-PURPOSE ACID LIMESCALE REMOVING CLEANER

DEFINITION

Water-based degreaser for all mechanical metal parts where it is important to avoid the risk of corrosion. Eliminates all traces of rust and limescale from metal and plastic surfaces.

ADVANTAGES

- · Improved effectiveness.
- Solvent-free. Free from VOCs, does not damage the ozone layer.
- Dissolves and eliminates all traces of rust and limescale deposits etc.
- · Excellent stripping compound.
- · Deoxidising properties
- Improved anti-corrosive power.
- Safe on plastics and varnishes.
- Does not contain enzymes or bacteria, so there is no risk of mutation or unpleasant odours.

APPLICATION FIELDS

- Particularly suited for cleaning metals (iron, steel, stainless steel) by hand or in a bath.
- Can be used in contact with aluminium.
- Clean unfinished or painted metal chassis (steel, stainless steel, copper).
- · Clean rotors, stators, and circuit breakers.
- · Clean wheels.
- · Clean sprayed metal run-off traces.
- Approved for cleaning vats and packaging machines in the food industry.

TECHNICAL CHARACTERISTICS

Aspect	
Colour	colourless
pH	1
Density at 20°C	1.180
Flash point	
VOCs = 0%.	

1/2 Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

ORAPI ® cannot know about every application for which the products are used nor their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.



TECHNICAL DATA SHEET

TDS 535 / Index 01 - 15/09/2014

INSTRUCTIONS FOR USE

This product can be used neat and cold or diluted in water.

For other uses, in a 2 to 15% solution with water, cold or hot (70°C max.), depending on the extent of soiling.

PACKAGING

1 kg container	ref. 2535I2	x 12
5 kg jerry can	ref. 2535J1	x 4
200 kg drum	ref. 2535U2.	x 1

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com