

ORASOLV A

DRY SOLVENT

FOOD INDUSTRIES
FAST-DRYING AND Kb value >80

DEFINITION

Solvent synthesised from refined solvents authorised for unintentional contact with foodstuffs.

ADVANTAGES

- Penetrates deeply and perfectly dissolves greasy deposits, glue and sludge.
- Does not lead to the oxidation of ferrous metals once product has dried.
- Dries very quickly. Does not leave an odour after drying.
- Soluble in water.
- Dry solvent, ideal for cleaning before bonding, paint-screening or painting.
- Contains no recycled solvents.
- Product formulated from ingredients authorised for use in products designed to clean equipment that may come into contact with foodstuffs, as per the Order of 08/09/1999 (Journal Officiel Français).
- Complies with new EU regulations and contains no chlorinated solvent, no fluoride solvent. Odourless.

APPLICATION FIELDS

- Specially formulated to rapidly and completely degrease all mechanical parts and metal surfaces in food-related industries.
- Removes adhesive, glue residue, and marker and pen marks. For use in food-related industries.

TECHNICAL CHARACTERISTICS

Aspect	Transparent liquid
Colour	Colourless
Odour	Alcohol; odourless after drying.
Density at 20°C	0.788
Rate of evaporation (internal standards)	3.5
Flash point	<21°C

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

ORAPI® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses."



INSTRUCTIONS FOR USE

Use product undiluted and cold: apply product with a brush or by soaking.

PACKAGING

650 ml aerosol	Ref. 4568 A4	x 12
5 L jerry-can	Ref. 2568 J1	x 4
200 L drum	Ref. 2568 U2	x 1

AUTHORISATION

-  NSF K1 Registration No. 140157
-  InS K1 Registered No.: 1795160

2/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com