



H.T. 600

ANTI-SEIZING PASTE

ALUMINIUM

DEFINITION

Aluminium-based, anti-seizing mounting and assembling paste, for oxidizing environments.

ADVANTAGES

This product, specially created to prevent seizing and corroding - whether caused by chemical, atmospheric or thermal reactions, ensures permanent protection against rust and oxidation. It significantly facilitates assembly and dismantling of some metal parts, reducing down time and maintenance manpower.

- Excellent resistance in an oxidizing environment.
- Good resistance to high temperatures.
- Prevents seizing and wrenching.
- Enables fluxing of metal and recovery of screw threads.
- Has a very low coefficient of friction.

APPLICATION FIELDS

Anti-corrosion and anti-rust: Forms a protective coating on bolts, cables, chains, and exterior equipment or equipment exposed to a corrosive environment.

At high temperatures: bolts and gaskets for cylinder heads, intake manifold runners, various manifolds, boiler valves, flange gaskets, valves, burners, laminator bolts and nuts, bolts, studs, oven conveyor chains, cellophane overwrapping machines, plastic injection moulding machines. Threads of screwed parts or gaskets exposed to very high temperatures for long periods are no longer affected by high temperatures and can be dismantled easily, without seizing or wrenching.

At normal temperatures: bolts, jib crane studs and rollers, metal heaters, bucket chains, naval and mining equipment, gaskets and packing.

On damaged threads, the H.T. 600 paste enables fluxing of metal and recovery of screw threads without use of taps or dies.

2/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

TECHNICAL CHARACTERISTICS

Aspect	pasty
Color	silvery
Density (NFT 60-101)	1,050 kg/m ³
Worked penetration (NFT 60-132)	310/340
Operating temperature	-40°C to +650°C
Dielectric conductivity	2.25 10 ⁸ . Ω ⁻¹ .m ⁻¹

INSTRUCTIONS FOR USE

Apply the paste to clean and dry parts.

PACKAGING

650 ml aerosol	Ref. 4601 A4	x12
200 g tube	Ref. 3601 T4	x12
250 ml tin with brush	Ref. 3601 B4	x 6
1 kg box	Ref. 3601 B7	x 6
5 kg bucket	Ref. 3601 S1	x 2

2/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com