



CT 615

WHITE EP GREASE

FOOD AND PHARMACEUTICAL INDUSTRIES

DEFINITION

CT 615 is a lubricant that is perfectly suited for use in food and food-processing industry.

ADVANTAGES

Specially formulated grease for use in environments in contact with water and humidity.
Demonstrates complete hot water- and vapour-resistance and adheres well to surfaces.
Withstands heavy loads and resists high temperatures.
CT 615 is composed of raw materials that comply with CODEX regulations.

APPLICATION FIELDS

Use in loaded main bearings and bearings turning at a speed of 500 – 5000 rpm.
Use in the manufacture and packaging of wine, beer, mineral water, biscuits, meats, fish, and throughout the food-processing industry.
Production and packaging of all food products.
Pharmaceutical and medical supplies industry, etc.
Lubricate hinges, runners, ball and socket heads, bearings, and more, to facilitate sliding and decrease friction.

TECHNICAL CHARACTERISTICS

Soap	Calcium complex
Colour	Opaque white
Texture	Smooth-running liquid
Density at 20°C (NFT 60-101)	0.94
Operating temperature	-20°C to +160°C; 200°C max.
Drop point (NFT 60-102)	>250°C
4-balls EP test (ASTM D 2596)	320 kg
Worked penetration after 60 strokes (ASTM 60-132)	295/335
NLGI Grade	1.5

INSTRUCTIONS FOR USE

Clean and degrease parts well before applying grease.

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

PACKAGING

100 g tube	Ref. 3615 T3	x 12
400 g cartridge	Ref. 3615 C4	x 12
1 kg box	Ref. 3615 B7	x 6
5 kg bucket	Ref. 3615 S1	x 2
50 kg drum	Ref. 3615 O4	x 1

NEW

400 g LUBE SHUTTLE cartridge	Ref. 3615 CL	x 12
------------------------------	--------------	------

AUTHORISATION

-  InS H1 Registered No.: 1795170

2/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com