



SILICONE SPRAY

LUBRICANT AND MOULD RELEASER

IDEAL FOR PLASTICS

DEFINITION

Silicone oil for mould releasing, lubrication and for anti adhering.

ADVANTAGES

Does leave stains, rings, or rubbery residue. Does not bond. Renews synthetic surfaces.
Provides excellent water-repellent power.
EDF-certified version available - **PMUC 19-208**

APPLICATION FIELDS

Lubricate metal-metal, metal-plastic, wood-metal assemblies, etc.
Can be used in the plastics industry for mould releasing, lubricating and thermo-welding, because of the product's numerous characteristics.
Use in printing works, the textile industry, wood and leather working, etc. Lubricate zippers, cutting machine blades (guillotine), door hinges, electrical systems protection, etc.

TECHNICAL CHARACTERISTICS

Aspect Translucent liquid
Colour Colourless
Operating temperature -50°C to +200°C
Dielectric strength 14 kV/mm
Not compatible with petroleum-based lubricants.

INSTRUCTIONS FOR USE

Spray an even layer onto the clean and dry surfaces of the parts to be treated. Repeat if necessary.
Disconnect equipment from power sources when using this product on electrical elements.
Do not use on parts that will be painted or bonded (use PEI 35 - 838 instead).

PACKAGING

650 ml aerosol	Ref. 4803 A4	x 12
PMUC – 650 ml aerosol	Ref. 6803 A4	x 12



1/1

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com