


858



2000 NUCL NF MULTI-PURPOSE NEAT CUTTING OIL

TAPPING, DRILLING, SAWING



DEFINITION

Ready-to-use cutting fluid with extreme-pressure agents, for all difficult manufacturing operations, whether manual or automatic.

Cutting fluid guaranteed to be chlorine-, sulphur- and fluorine-free.

ADVANTAGES

Can be used for a variety of operations, tools and worked metals, Prevents seizing and chatter. Provides excellent lubrication. Extreme-pressure additives, anti-corrosion, anti-wear. Bonds well to surfaces. Demonstrates excellent shearing strength. Avoids reworking and rejections, Improves output, Avoids tools overheating, Contains no silicone.

APPLICATION FIELDS

Designed for the lubrication of cutting tools. Produces regular chips and eliminates wrenching and scratches. Recommended for tapping, milling, drilling, cutting, sawing, and pressing stainless steel and special steels.

TECHNICAL CHARACTERISTICS

Aspect	transparent liquid
Colour	pale yellow
Viscosity at 40°C (ASTM D445)	21 cSt
Density at 20°C (NF T 60 101)	0.8
CI, F, S	< 200 ppm

1/2 Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

ORAPI © cannot know about every application for which the products are used nor their conditions of use. ORAPI © shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI © renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability of ra certain purpose, resulting from the sale or use of its products. In particular, ORAPI © renounces any claims for incidental or consequential damages whatsoever, including financial operating losses



INSTRUCTIONS FOR USE

Apply to taps or drills or the part to be machined before beginning the operation. (Re-apply if needed).

PACKAGING

Aerosol 650 ml 500 ml container 5 litre jerry can 200-litre drum Ref. 6858 A4 Ref. 6858 I1 Ref. 6858 J1 Ref. 6858 U2 x 12

x 12

Χ4

19-083 19-0527 (new code December 2014)

Head office Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

2/2

ORAPI © cannot know about every application for which the products are used nor their conditions of use. ORAPI © shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI © renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability of ra certain purpose, resulting from the sale or use of its products. In particular, ORAPI © renounces any cincidental or consequential damages whatsoever, including financial operating losses