



FILDUC 1879

MULTI-PURPOSE NEAT CUTTING OIL

**TAPPING, DRILLING, SAWING
ONLY 2% VOC**

DEFINITION

Ready-to-use cutting fluid with extreme-pressure agents, for all difficult manufacturing operations, whether manual or automatic.

ADVANTAGES

- Can be used for a variety of operations, tools and worked metals.
- Prevents seizing and chatter.
- Provides excellent lubrication.
- Extreme-pressure additives, anti-corrosion, anti-wear.
- Bonds well to surfaces.
- Demonstrates excellent shearing strength.
- Avoids reworking and rejections.
- Improves output.
- Avoids tools overheating.
- Contains no silicone.

APPLICATION FIELDS

- FILDUC 1879 is designed for the lubrication of cutting tools.
- It allows cuts to be regular and eliminates wrenching and scratches.
- FILDUC 1879 is recommended for tapping, milling, drilling, cutting, sawing, and pressing stainless steel and special steels.
- Do not use on metals or alloys that contain copper (risk of staining).

TECHNICAL CHARACTERISTICS

Aspect	Viscous liquid
Colour	Brown
Viscosity at 40°C (ASTM D445)	510 cSt
Density at 20°C (NF T 60 101)	0.97
VOC content	< 2%

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

INSTRUCTIONS FOR USE

Apply to taps or drills or the part to be machined before beginning the operation.
(Re-apply if needed).

For difficult applications, such as on vertical or upside-down surfaces, this product is also available as a paste: 886 – TA 1800.

PACKAGING

650 ml aerosol	Ref. 4859 A4	x 12
125 ml oil can	Ref. 2859 R1	x 12
5 L jerry-can	Ref. 2859 J1	x 4
20 L drum	Ref. 2859 O1	x 1
200 L drum	Ref. 2859 U2	x 1

2/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com